

FEATURES

The output voltage can be adjusted to 36V
 Low dynamic output impedance ,its typical value is 0.2Ω
 Trapping current capability is 1 to 100mA
 The typical value of the equivalent temperature factor in the whole temperature scope is 50 ppm/°C
 The effective temperature compensation in the working range of full temperature
 Low output noise voltage
 Fast on -state response

SOT-23



1. REFERENCE

2. CATHODE

3. ANODE

ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	SYMBOL	VALUE	UNITS
Cathode Voltage	V_{KA}	37	V
Cathode Current Range (Continuous)	I_{KA}	-100~+150	mA
Reference Input Current Range	I_{ref}	0.05~+10	mA
Power Dissipation	P_D	300	mW
Operating temperature	T_{opr}	0-70	°C
Storage temperature Range	T_{stg}	-65~+150°C	°C

ELECTRICAL CHARACTERISTICS ($T_{amb}=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Reference Input Voltage	V_{ref}	$V_{KA}=V_{REF}$, $I_{KA}=10\text{mA}$	2.450	2.5	2.550	V
Deviation of reference input Voltage Over temperature (note)	$\Delta V_{ref}/\Delta T$	$V_{KA}=V_{REF}$, $I_{KA}=10\text{mA}$ $T_{min}\leq T\leq T_{max}$		4.5	17	mV
Ratio Of Change in Reference Input Voltage to the change in Cathode Voltage	$\Delta V_{ref}/\Delta V_{KA}$	$I_{KA}=10\text{mA}$ $\Delta V_{KA}=10\text{V}\sim V_{REF}$		-1.0	-2.7	m V/V
		$\Delta V_{KA}=36\text{V}\sim 10\text{V}$		-0.5	-2.0	m V/V
Reference Input Current	I_{ref}	$I_{KA}=10\text{mA}$, $R_1=10\text{K}\Omega$ $R_2=\infty$		1.5	4	μA
Deviation Of Reference Input Current Over Full Temperature Range	$\Delta I_{ref}/\Delta T$	$I_{KA}=10\text{mA}$, $R_1=10\text{K}\Omega$ $R_2=\infty$ $T_A=\text{full Temperature}$		0.4	1.2	μA
Minimum cathode current for regulation	$I_{KA(min)}$	$V_{KA}=V_{REF}$		0.45	1.0	mA
Off-state cathode Current	$I_{KA(OFF)}$	$V_{KA}=36\text{V}$, $V_{REF}=0$		0.05	1.0	μA
Dynamic Impedance	Z_{KA}	$V_{KA}=V_{REF}$, $I_{KA}=1$ to 100mA $f\leq 1.0\text{KHz}$		0.15	0.5	Ω

Note: $T_{MIN}=0^{\circ}\text{C}$, $T_{MAX}=+70^{\circ}\text{C}$

CLASSIFICATION OF V_{ref}

Rank	0.5%	1%	2%
Range	2.487-2.512	2.475-2.525	2.450-2.550

Typical Characteristics

